



Time Electronics

7018 Differential Pressure Calibrator

DENVER
metrología electrónica, S.L.



- 0.2, 2, 5 and 10bar versions available
- Accuracy 0.04% of full scale
- Pneumatic
- Calibrate DP transmitters, gauges & more
- Loop current measure
- 24/36V loop power
- Over-pressure alarm
- RS-232 serial interface
- EasyCal software compatible
- Mains or battery powered

DESCRIPTION

The 7018 is a differential pressure calibration system suitable for field and laboratory calibration work of both differential pressure and electrical process loop signals. The instrument is designed for very stable measurement of differential pressures between its two output ports, enabling the calibration of differential pressure gauges, transducers, and transmitters. There are five available versions, according to the required range, either 0.2, 2, 5, or 10bar.

Features include a 4.5 digit LCD display with 4 selectable pressure units plus mA, zeroing switch, and two quick release connector ports (Hi and Lo for differential pressure input) that are situated on the front panel of the unit. Best accuracy is 0.04% of full scale.

For process signal calibration the loop signal is displayed on the LCD display to 0.05% accuracy. Loop drive supply (24V or 36V) is also provided. Both pressure and loop signal can be displayed at the same time to speed up the calibration of pressure transmitters. Additionally a continuity function is available for testing for open circuit loops.

Power is via internal rechargeable cells (24 hours typical use) with a built-in mains charger. The unit can be powered directly from the mains if required. The 7018 is housed in an impact resistant safety case that provides protection and increased durability. Pressure connections are on the front panel and the instrument is supplied with a pressure hose, electrical test lead, 2 electrical probes and 2 crocodile clips.

OPTIONS

For the 7018, input pressure can be generated by the 7090 pneumatic hand pump (-950mbar to 40bar). Other pumps and digital pressure gauges are also available.

For process control signal simulation Time Electronics' handheld 7006 Loop-Mate is available as an option. It provides 4 - 20mA and 0 - 10V signals at levels of 0%, 10%, 25%, 50%, 75%, 90%, 100%. It can also step through these set points automatically to allow hands free calibration. It is battery powered and can be stored in the 7018's supplied carry pouch. See separate datasheets for more information.

The 7018 is fitted with RS232 connection as standard. Display readback can be performed using EasyCal calibration software. With comprehensive features EasyCal can simplify and speed up calibration procedures. Easily produce calibration certificates and reports to international quality standards.



7018 Specifications

TECHNICAL SPECIFICATION

PRESSURE

Specifications are for 1 year at 23°C ±5°C. Accuracy includes linearity and long term effects. All accuracies are ±1 digit. For operation outside specified temperature range, apply 70ppm per °C

Range (bar)	0 to ±0.2	0 to ±2	0 to ±5	0 to ±10
Accuracy (% of fs)	0.1	0.04	0.04	0.04
Resolution (bar)	0.01mb	.0001	0.001	0.001

Units 0.2bar version: mbar, PSI, kg/cm2, cmWg and mA.
 2, 5, and 10bar versions: bar, PSI, kg/cm2, cmWg and mA.
 Maximum Static Pressure 10bar
 Sensor Piezo-resistive - stainless steel diaphragm
 Over pressure warning 1.2 x range full scale - audio and visual (on LCD) warning
 Fittings Quick Release

ELECTRICAL

Range Loop current measurement 0 to 200mA
 Resolution 10µA
 Resistance Loop load 5Ω
 Accuracy 0.05% of reading ±1 digit
 Loop Drive 24V or 36V switch selectable, 50mA max - isolated and with short circuit protection
 Continuity Threshold: 100Ω with audio and visual warning
 Terminals 4 mm industry standard terminal posts

GENERAL SPECIFICATION

Power Source Internal rechargeable NiMH batteries, or mains supply (230V or 110V 50/60Hz)
 Battery Life 24 hrs of typical usage between charges
 Display 7 segment LCD display with 'Low Battery' warning indicator
 Interfaces RS-232 for readback and re-calibration (software not supplied)
 Case Structural resin which is weather-proof to IP66 standard
 Dimensions W270 x H175 x D250mm
 Weight 3kg
 Supplied with 1 pressure hose: Quick release fitting
 Electrical Test Lead: Twin flexible lead, terminated with 4 off 4mm gold plated plugs
 Electrical probes: 2 off low voltage probes and 2 crocodile clips. Mains power lead.
 Optional Extras Pneumatic hand pump, gauges, loop simulators, EasyCal calibration software, spare fuses, and calibration certificates traceable to NPL and UKAS

ORDERING INFORMATION

7018 **Differential Pressure Calibrator** (+ pressure range code shown below)

Range (bar)	0.2	2	5	10
Option Code	7100	7101	7102	7103

7090 Pneumatic Hand Pump (-950mbar to 40bar). See separate datasheet for options.
 7006 Loop-Mate 1: Loop Current Simulator
 ECFLA EasyCal Calibration Software. See separate datasheet for further information.
 C178 Factory Calibration Certificate (NPL traceable)
 C190 UKAS Calibration Certificate (ISO 17025)

Due to continuous development Time Electronics reserves the right to change specifications without prior notice.

Time Electronics Ltd, Unit 11 Sovereign Way, Botsford, Kent, TN9 1RH. United Kingdom.

T: +44 (0) 1732 355993 F: +44 (0) 1732 355994 www.timeelectronics.co.uk

www.tin

Tel: +34 91 569 8006
 info@denver.es - www.denver.es

v1d 7/4/13